

PROFESSIONAL

ELETTRICO / ELECTRIC

# KX

 3005 - 4005 - 4055

**ACCESSORI STANDARD**  
**STANDARD ACCESSORIES**

 920mm  
 Lancia con pistola automatica da 920 mm.  
 920 mm. lance with automatic trigger gun

 Tubo alta pressione da 10 metri  
 10 meters high pressure hose

Dimensioni tubo / Hose dimensions

<b>R1 5/16</b>	<b>R2 5/16</b>
3005	4005 - 4055

**CARATTERISTICHE**  
**FEATURES**

**TSD**  
 TOTAL STOP

**SMS**  
 SAFE MANOMETER SYSTEM

**HT - HIGH TEMPERATURE**  
 Disponibile versione HT  
 HT version available

**IMBALLAGGIO / PACKAGING**


75x60x77 cm



73 kg


**CARATTERISTICHE / FEATURES**

Codice Code	Modello Model	Portata Flow Rate lt/min	Pressione / Pressure		Pompa / Pump		Potenza / Power		Tensione Voltage Volts	Frequenza Frequency Hertz	Fase Phase
			Bar		rpm		HP	kW			
3.023.14.355	<b>KX3005</b>	10	150		1450		3	2.2	230 V	50	1
3.023.14.343	<b>KX4005</b>	15	200		1450		7.5	5.5	400 V	50	3
3.023.14.366	<b>KX4055</b>	21	150		1450		7.5	5.5	400 V	50	3

Disponibile anche a 60Hz / Available at 60Hz

PROFESSIONAL

ELETTRICO / ELECTRIC

# KX

 3005 - 4005 - 4055

**MOTORE / ENGINE**

 Motore elettrico MAZZONI senza  
 manutenzione asincrono monofase serie  
 MEC, con termiche sugli avvolgimenti.  
 MAZZONI MEC series maintenance-free electric  
 induction motor with thermic protection on the  
 windings

 Giunto elastico  
 Elastic coupling

**POMPA / PUMP**

 Pompa professionale in linea (a bielle) con  
 testata in ottone e tre pistoni in ceramica.  
 In line professional pump (with connecting  
 rods), brass head, and three ceramic pistons.

**DETTAGLI / DETAILS**

 Ruota anteriore girevole  
 Third pivoting wheel

**CARATTERISTICHE TECNICHE / TECHNICAL FEATURES**

- |   |                                   |
|---|-----------------------------------|
| 1 Telaio in acciaio INOX                    | Stainless steel frame             |
| 2 Valvola bypass Mazzoni                    | Mazzoni bypass valve              |
| 3 Interruttore On-Off                       | On-Off                            |
| 4 Tanica detergente da 5 l                  | 5 l detergent tank                |
| ✓ Contatore interno                         | Internal hour meter               |
| ✓ Aspirazione detergente in bassa pressione | Detergent suction in low pressure |

**ACCESSORI OPZIONALI / OPTIONAL ACCESSORIES**
● 3005 ● 4005 ● 4055

 3.020.22.030 ●  
 3.020.22.030 ● - 3.020.22.056 ●  
 Ugello rotativo / Turbo nozzle

 3.061.04.002 ● ● ● ●  
 Lettore ore / Hours reader

 3.020.22.038 ● - 3.020.22.024 ●  
 Kit sabbatura / Sandblasting Kit

 2.071.04.019 ● ● ● ●  
 Avvolgitubo / Hose reel

 KX con avvolgitubo e pistola  
 KX with gun and hose reel
