




## Optimal ergonomics, reliable cleaning

- High efficiency 4 pole motors
- EcoPower boiler with EcoMode function
- Brass pump head
- 3 ceramic coated pistons
- Pressure activated unloader system
- Simple fuel level sight
- Easy access to components
- Easy pump oil service functions with tank and oil sight
- Innovative design with 4 big wheels
- Easy to transport, can even be pushed/pulled across uneven surfaces

The MH 3M series takes mid-range hot water high pressure washers to a new level, meeting the latest productivity demands in the market. The MH 3M is equipped with our semi industrial NA4 pump with 3 ceramic coated pistons and a high efficiency 4 pole motor. It offers ideal performance levels for general hot water cleaning and the efficient EcoPower Boiler.



TECHNICAL DATA	MH 3M-140/580 PA	MH 3M-160/770 PA
Pump pressure (bar/MPa)	140/14	160/16
Cleaning impact (kg/force)	2.8	3.6
Water flow Qmax/Qiec (l/h)	580/580	770/700
Pump (RPM)	1450	1450
Water temperature (water/steam) (°C)	80	80
Max. inlet temperature (°C)	40	40
Fuel consumption at ΔT=45°C (kg/h)	2.6	3.1
Fuel tank (l)	15	15
Length x width x height (mm)	1010x700x1016	1010x700x1016
Weight (kg)	114	133
Power consumption (kW)	3.6	4.7
Voltage/phase/frequency/current (V~/HZ/A)	230/1/50/16	400/3/50/8
Ceramic coated pistons	3	3
El cable (m)	5	5
Nozzle size	.0370	.0400
<b>FEATURES</b>		
Fuel tank	•	•
Delayed automatic start stop	•	•
Fuel sight from outside	•	•
Eco mode feature	•	•
2 lance holder	•	•
Large wheel – 4 pcs.	•	•
Anti Stone	•	•
<b>STANDARD EQUIPMENT</b>		
ERGO COUPLING KIT	101119496	101119496
HOSE NOZZLE 20R3/4	61369	61369
10M WIRE HOSE DN6	301002275	301002275
ERGO 2000 STANDARD W. HOSE SWIVEL	106403122	106403122
UNIVERSAL PLUS LANCE 940 BEND W/O NOZZ	106403036	106403036
NOZZLE 0370 INDICATION RING BRONZE	101119737	
NOZZLE 0400 INDICATION RING METAL GREY		101119738
<b>ITEM NO.</b>	<b>107146895</b>	<b>107146903</b>