



Powerful and safe dust extractor for hazardous dust

- InfiniClean™ - Automatic filter cleaning system with minimized performance loss
- PTFE long-life filter with non-stick membrane and minimum 99.9% filtration efficiency
- Push&Clean™ - Semi-automatic filter cleaning system on selected models.
- Dust class M and H certification including Asbestos
- Unique dual filter solution available for H-class/HEPA - including 3-stage filtration
- Flow sensor with combined acoustic and LED warning
- 30 liter container with steel castors and robust bumper.
- MultiFit accessory system for the ultimate in task flexibility
- Flexible rubber straps, tool box storage and optional trolley handle for convenient storage and transport
- Optional motor cooling filter, exhaust air collector and Long-Life filter bag

The ATTIX 33 M/H dust extractor series sets a standard for design and feature level of the Nilfisk wet & dry vacuum portfolio. With innovative filtration system, improved performance, robust design and dust class M/H certification, this range represents a superior solution for professional customers looking for a reliable machine to protect workers health and safety. ATTIX 33 M/H comes with more suction power, sealed dust system, automatic filter cleaning and several other user benefits - designed to meet the tough requirements in building & constructions and other industries when picking up hazardous dust.



| TECHNICAL DATA | ATTIX 33-2H IC | ATTIX 33-2H PC | ATTIX 33-2M IC | ATTIX 33-2M PC |
|-------------------------------------|------------------------|------------------------|------------------|------------------|
| Airflow rate (l/min.) | 4500 | 4500 | 4500 | 4500 |
| Vacuum (mbar/kPa) | 250/25 | 250/25 | 250/25 | 250/25 |
| Power Pmax (W) | 1400 | 1400 | 1400 | 1400 |
| Power Pic (W) | 1200 | 1200 | 1200 | 1200 |
| Working sound level (dB(A)) | 60 | 60 | 60 | 60 |
| Container volume (l-max) | 30 | 30 | 30 | 30 |
| Mains connection (V~/Hz/A) | 230/1/50-60/16 | 230/1/50-60/16 | 230/1/50-60/16 | 230/1/50-60/16 |
| Length x width x height (mm) | 565x385x520 | 565x385x520 | 565x385x520 | 565x385x520 |
| Weight (kg) | 14.5 | 14.5 | 14.5 | 14.5 |
| El cable (m) | 7.5 | 7.5 | 7.5 | 7.5 |
| Main filter type | PTFE/Cellulose H-class | PTFE/Cellulose H-class | PTFE M-class | PTFE M-class |
| Filter cleaning system | InfiniClean | Push&Clean | InfiniClean | Push&Clean |
| FEATURES | | | | |
| Softstart | • | • | • | • |
| Dual filter system | • | • | • | • |
| Anti-static system | • | • | • | • |
| Automatic On/Off-elec. tools | • | • | • | • |
| Disposal bag 1 pcs | | | • | |
| Fleece filter bag 1 pcs | | | • | • |
| Safety filter bag 1 pcs | • | • | | |
| STANDARD EQUIPMENT | | | | |
| HOSE Ø36X4000 MM AS RED | 107413544 | 107413544 | | |
| CURVED HAND TUBE Ø36MM SS | 46691 | 46691 | 46691 | 46691 |
| EXTEN TUBE Ø36 2X505MM SS | 107408074 | 107408074 | 107408074 | 107408074 |
| TOOL ADAPTER D27 QUICKSYSTEM | 302000535 | 302000535 | 302000535 | 302000535 |
| FLOOR NOZZLE Ø36X300MM | 302002331 | 302002331 | | 302002331 |
| FLOOR NOZZLE Ø36X360MM WET/DRY | | | 60356 | |
| CREVICE NOZZLE D36X200 | 29541 | 29541 | 29541 | 29541 |
| HOSE Ø32X4000MM AS RED | | | 107413543 | 107413543 |
| FILTER ELEMENT Ø140X75 H-CLASS/HEPA | 107413555 | 107413555 | | |
| FLAT FILTER PTFE M-CLASS 1 PCS | 107413540 | 107413540 | 107413540 | 107413540 |
| FLEXIBLE STRAP SET 2 PCS | 107413553 | 107413553 | 107413553 | 107413553 |
| ITEM NO. | 107412184 | 107412183 | 107412180 | 107412179 |