



Stationary 2-pump high pressure washers for heavy cleaning tasks

- NA6, C3 and new NA6+ high-quality motor pumps with brass pump heads
- 1450 rpm; 4 full ceramic pistons and double roller bearings
- Working pressure up to 180 bar
- Water flow up to 2x2500 l/h
- 70°- 85°C hot water inlet for max. cleaning efficiency
- Innovative hard foam cabinet
- Built on powder-coated steel frame
- Foam cabinet reduces the noise level
- Incl. Low pump oil warning lamps, Service warning lamp, Hour counter, Low pump oil safety

Designed for large cleaning tasks SC DUO 6P, 7P & 8P are ideal for agriculture with milking sheds, sties, and stables. Food and pharma industry with processing equipment, conveyors, and tanks. Shipping and industry with ship decks, bulkheads, and industrial equipment. Even oil and grease can be removed easily thanks to the hot water inlet.

Offers you the flexibility of being either one user – or two working together. Cleaning efficiency is maximized by a 4-piston long-life motor pump accepting both cold and hot water up to 85°C.



TECHNICAL DATA	SC DUO 6P-170/3220	SC DUO 7P-180/2400	SC DUO 8P-160/5000	SC DUO 8P-180/4000
Recommended avg. hours of use per day	5	6	7	7
Pump pressure (bar/MPa)	170/17	180/18	160/16	180/18
Cleaning impact (kg/force)	15.8	12.1	23.8	19.5
Water flow Qmax/Qiec (l/h)	3220/3000	2400/2240	5000/4800	4000/3600
Max. inlet temperature (°C)	80	85	80	80
Length x width x height (mm)	355x860x1000	355x860x1000	355x860x1000	355x860x1000
Weight (kg)	180	160	212	212
Nozzle size	.0900	.0640	.1500	.1200
Number of pumps	2	2	2	2
FEATURES				
Hour Meter	•	•	•	•
Pump oil warning system	•	•	•	•
Service indicator	•	•	•	•
Intelligent pump control system	•	•	•	•
Foam Cabinet, EPP	•	•	•	•
Motor on-off lamp	•	•	•	•
Service warning lamp	•	•	•	•
STANDARD EQUIPMENT				
NIPPLE F/QUICK COUPLING 3/8 SS	1603101	1603101	1603101	1603101
QUICK COUPLING 3/4 W/GASKET	1602945	1602945		1602945
ITEM NO.	107340600	107340620	107340611	107340610