




Compact and innovative - for low intensity cleaning applications

- EcoPower boiler with >92% efficiency and reduced fuel costs
- Robust steel frame
- Compact, vertical design reducing storage footprint
- Easy to use control panel... all controls in one place
- Ergo accessory system
- Machine protection against through low fuel safety, exhaust gas sensor, flame sensor
- Max. Inlet temperature 40°C

MH 1C is a compact and innovative hot water unit ideal for low intensity and infrequent cleaning applications around small garages or farms, car dealers or by tradesmen and craftsmen.



| TECHNICAL DATA | MH 1C-110/600 |
|---|------------------|
| Pump pressure (bar/MPa) | 110/11 |
| Cleaning impact (kg/force) | 2.3 |
| Water flow Qmax/Qiec (l/h) | 600/540 |
| Pump (RPM) | 2800 |
| Water temperature (water/steam) (°C) | 80 |
| Max. inlet temperature (°C) | 40 |
| Fuel consumption at ΔT=45°C (kg/h) | 2.4 |
| Fuel tank (l) | 17 |
| Length x width x height (mm) | 607x688x1000 |
| Weight (kg) | 94 |
| Power consumption (kW) | 2.8 |
| Voltage/phase/frequency/current (V~/HZ/A) | 230/1/50/12 |
| Detergent tank (l) | 5 |
| Stainless steel pistons | 3 |
| El cable (m) | 5 |
| Nozzle size | .0400 |
| FEATURES | |
| Detergent tank | • |
| Single-phase | • |
| EcoPower boiler-high efficiency | • |
| Compact design | • |
| Service indicator | • |
| Automatic start/stop | • |
| Flame sensor | • |
| STANDARD EQUIPMENT | |
| ERGO COUPLING KIT | 101119496 |
| GARDENA COMPATIBLE MALE 3/4" ACCESSORY | 106404529 |
| ERGO 2000 STANDARD W. HOSE SWIVEL | 106403122 |
| FLEXOPOWER PLUS 990 BEND W/O NOZ. | 106402281 |
| NOZZLE 0400 INDICATION RING METAL GREY | 101119738 |
| ITEM NO. | 107145000 |